

C25C

IC-CUSHION LPG/DUAL FUEL
 4000 / 5000 / 6000 / 6500 lbs.
 (2000 / 2500 / 3000 / 3200 kg)

GEN2



STANDARD SPECIFICATIONS

C20/25/30/32C

Manufacturer's Designation		C20CL	C25CL	C30CL	C32CL
Load Capacity / Rated Load	lbs(kg)	4000 (2000)	5000 (2500)	6000 (3000)	6500 (3200)
Height Overhead Guard	in(mm)	82.8 (2105)	82.8 (2105)	82.8 (2105)	82.8 (2105)
Width	in(mm)	42.5 (1080)	42.5 (1080)	43.7 (1110)	45.4 (1154)
Right Angle Stack (add load length and clearance)	in(mm)	94.5 (2399)	96.8 (2459)	99.2 (2519)	101.4 (2575)
Outside Turning Radius	in(mm)	77.8 (1975)	80.1 (2035)	82.3 (2090)	83.9 (2130)
Travel speed loaded / unloaded	mph (kph)	10.0 / 10.1 (16.1 / 16.2)	10.0 / 10.1 (16.1 / 16.2)	10.0 / 10.1 (16.1 / 16.2)	10.0 / 10.1 (16.1 / 16.2)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Hyundai / 70.4 (52.5) @ 2650	Hyundai / 70.4 (52.5) @ 2650	Hyundai / 70.4 (52.5) @ 2650	Hyundai / 70.4 (52.5) @ 2650

STANDARD FEATURES

2.4 liter engine • EPA compliant • Electronic governor • Fuel system diagnostics • Low LPG warning light • Standard, Triple, Hi-Lo and Quad uprights • Full range of lift heights available • High visibility “silent staging” uprights • Automatic engine shutdown protection • Two-pedal inch-brake system • High capacity cooling system • Auxiliary valve • Routine maintenance points are highly accessible • Isolated operator cell • Clark safety seat • Tilt steering wheel • Clark Information Center, full LED/digital display • Full access clamshell hood • Headlights - overhead guard mounted



For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com.