

S SERIES

S25

20/25/30/35

IC-PNEUMATIC LPG/DUAL FUEL
4000 / 5000 / 6000 / 7000 lbs.
(2000 / 2500 / 3000 / 3300 kg)



STANDARD SPECIFICATIONS

20/25/30/35

| Manufacturer's Designation | | S20D | S25D | S30D | S35D | S20L | S25L | S30L | S35L |
|--|-------------|---------------------------|---------------------------|---------------------------|---------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| Load Capacity / Rated Load | lbs(kg) | 4000 (2000) | 5000 (2500) | 6000 (3000) | 7000 (3500) | 4000 (2000) | 5000 (2500) | 6000 (3000) | 7000 (3500) |
| Height Overhead Guard | in(mm) | 85.2 (2165) | 85.2 (2165) | 85.8 (2180) | 86.6 (2200) | 85.2 (2165) | 85.2 (2165) | 85.8 (2180) | 86.6 (2200) |
| Width | in(mm) | 45.7 (1160) | 45.7 (1160) | 48.1 (1220) | 48.9 (1242) | 45.7 (1160) | 45.7 (1160) | 48.1 (1220) | 48.9 (1242) |
| Right Angle Stack (Add Load Length and Clearance) | in(mm) | 107.5 (2730) | 110 (2795) | 115.2 (2925) | 118 (2997) | 107.5 (2730) | 110 (2795) | 115.2 (2925) | 118 (2997) |
| Outside Turning Radius | in(mm) | 89.2 (2265) | 91.7 (2330) | 96.5 (2450) | 98.5 (2502) | 89.2 (2265) | 91.7 (2330) | 96.5 (2450) | 98.5 (2502) |
| Travel speed Loaded & Unloaded | mph (kph) | 10.3 (16.6) / 11.0 (17.7) | 10.1 (16.3) / 10.9 (17.6) | 10.9 (17.5) / 11.5 (18.6) | 11.8 (19) / 12.0 (19.3) | 10.7 (17.2) / 11.4 (18.3) | 10.4 (16.8) / 11.3 (18.2) | 11.2 (18.1) / 11.9 (19.3) | 11.2 (18.1) / 11.6 (18.7) |
| Power Unit | HP(KW) @rpm | ISUZU 61.7 (46) @ 2400 | ISUZU 61.7 (46) @ 2400 | ISUZU 61.7 (46) @ 2400 | ISUZU 61.7 (46) @ 2400 | FORD2.5 69.7 (52) @ 2500 | FORD2.5 69.7 (52) @ 2500 | FORD2.5 69.7 (52) @ 2500 | FORD2.5 69.7 (52) @ 2500 |

Standard Features

- FORD 2.5L Balanced Engine • EPA Compliant • Standard, Triple, Hi-Lo and Quad Uprights • Full Range of Lift Heights • High Visibility "Silent Staging" Uprights • Two-Pedal Inch-Brake System • Single Speed Transmission • Force-Cooled Wet Disc Brakes • Automatically-Applied Parking Brake • Hood Mounted Control Levers • LED Headlights OHG Mounted • Speed Limiter • Traction Disable Seat Switch • Operator Presence System • Raised Air Intake • Copper Open Core Radiator • High Capacity Cooling System • 5" Color LCD Digital Display • Automatic Engine Shutdown System • Low Fuel Warning Light • Power Steering • Tilt Steering Wheel • Grab Bar Handle with Horn Button • Steering Wheel Spinner Knob • Full Suspension Vinyl Seat with Hip Restraints • Orange Seatbelt • Drink Holder • Convenience Console

For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com.

